



OPEN-TOP VISE. An angled, open-top vise allows for the passage of larger tooling. Because of the large opening, operators can also use it to break out tooling.



STACKABLE ROD BOXES. Stackable rod boxes are easy to use with a single pin and patent-pending auto lock.



DRILL EFFICIENTLY. The D100x140 S3 features the DigiTrak[®] Aurora[™] full-color touchscreen display, delivering an engaging experience which helps make a driller's day more productive.



OPTIONAL ONBOARD CRANE. Choose the optional onboard knuckleboom style crane to reduce the amount of support equipment needed onsite.



INCREASE YOUR RANGE. Unique four-bar linkage rack and additional pads allow operators to set up entry angles of 11 - 24° — increasing range attainable with tracks fully on ground.



FIRESTICK® DRILL ROD. Experience the difference that has made one-piece, forged Firestick drill rod the industry benchmark.



D100x140 S3 NAVIGATOR® HORIZONTAL DIRECTIONAL DRILL

GENERAL WEIGHTS AND DIMENSIONS

 Transport length [15' (4.6 m) rod option]: 29.8' (9.1 m)

 Transport length [20' (6.1 m) rod option]: 34.2' (10.4 m)

 Transport width: 100" (254 cm)

 Min transport height: 11.3' (3.4 m)

 Weight [15' (4.6 m) rod option]: 49,800 lb (22,588.9 kg)

 Weight [20' (6.1 m) rod option]: 57,220 lb (25,954.6 kg)

ENGINE

Make: CAT Fuel type: Ultra-low sulfur diesel Gross power rating: (205 kW) Max engine rpm: 2200 rpm Cooling method: Liquid Aspiration: Twin turbo charged Emissions compliance: Tier 4 Final

OPERATIONAL

Thrust/Pullback: 100,000 lb (444.8 kN) Max carriage speed: 175 ft/min (53.3 m/min) Max spindle torque (low at max engine rpm): 14,000 ft-lb (18,981.5 Nm) Max ground drive speed: 2.8 mph (4.5 km/h) Noise level: 84 d(B)a

FLUID CAPACITIES

Fuel tank: 120 gal (454.3 L) Engine crankcase with filter: 4.4 gal (16.7 L) Hydraulic tank: 90 gal (340.7 L)

HYDRAULIC SYSTEM

Auxiliary pump flow at max engine rpm: 13.4 gpm (50.7 L/min) Auxiliary pump relief pressure: 3000 psi (206.8 bar) Thrust/Pullback pump flow at max engine rpm: 53 gpm (200.6 L/min) Thrust/Pullback pump relief pressure: 6000 psi (413.7 bar) Rotation pump flow at max engine rpm: 96 gpm (363.4 L/min) Rotation pump relief pressure: 5400 psi (372.3 bar)



DRILLING FLUID SYSTEM

Max flow: 230 gpm (870.6 L/min) Max pressure: 1000 psi (68.9 bar)

OPTIONAL CRANE

Weight: 2800 lb (1270.1 kg) Max lifting capacity at 13' (4 m): 5070 lb (2299.7 kg) Max lifting capacity at 19.5' (5.9 m): 4200 lb (1800.8 kg) Rotation: 400° Max reach: 19.5' (5.9 m) Remote: Radio

FEATURES

Drilling lights: Standard Stakedown system: Optional Remote ground drive control: Optional Strike alert: Standard Remote lockout: Standard

DRILL PIPE OPTION ONE

Type: Firestick drill rod Length: 15' (4.6 m) Joint diameter: 4.375" (11.1 cm) Pipe diameter: 3.5" (8.9 cm) Weight: 261 lb (118.4 kg) Min bend radius: 197' (60 m) Rod carrying capacity: 135' (41.1 m) with permanent rod box, 270' (82.3 m) with stacked box

DRILL PIPE OPTION TWO

Type: Firestick drill rod Length: 20' (6.1 m) Joint diameter: 4.4" (11.2 cm) Pipe diameter: 3.5" (8.9 cm) Weight: 360 lb (163.3 kg) Min bend radius: 197' (60 m) Rod carrying canacity: 180' (54.9 m) with permanent rod box

Rod carrying capacity: 180' (54.9 m) with permanent rod box, 360' (109.7 m) with stacked box



Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Firestick and Navigator are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Aurora and DigiTrak are trademarks of Digital Control Incorporated. © 2014 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.